



Product Service

Attestation of Conformity

No. E8A 070228 0088 Rev. 01

Holder of Certificate: **BYD CO LTD.**
Baolong Industrial Town, 1 Bao Ping Rd.
518116 Longgang, Shenzhen, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Batteries**
(Rechargeable Li-ion Battery System)

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 647711710702

Date, 2019-04-02 (Tony Liu)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany



ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT



Product Service

Attestation of Conformity

No. E8A 070228 0088 Rev. 01

Model(s):

Battery-Box H 5.1, Battery-Box H 6.4, Battery-Box H 7.7,
 Battery-Box H 9.0, Battery-Box H 10.2, Battery-Box H 11.5,
 Battery-Box H 5.1(AU), Battery-Box H 6.4(AU),
 Battery-Box H 7.7(AU), Battery-Box H 9.0(AU),
 Battery-Box H 10.2(AU), Battery-Box H 11.5(AU)

Description of Object:

Nominal Voltage:

Battery-Box H 5.1, Battery-Box H 5.1(AU): 204.8V d.c.
 Battery-Box H 6.4, Battery-Box H 6.4(AU): 256V d.c.
 Battery-Box H 7.7, Battery-Box H 7.7(AU): 307.2V d.c.
 Battery-Box H 9.0, Battery-Box H 9.0(AU): 358.4V d.c.
 Battery-Box H 10.2, Battery-Box H 10.2(AU): 409.6V d.c.
 Battery-Box H 11.5, Battery-Box H 11.5(AU): 460.8V d.c.

Recommended Charging

Voltage By Manufacturer:

Battery-Box H 5.1, Battery-Box H 5.1(AU): 224V d.c.
 Battery-Box H 6.4, Battery-Box H 6.4(AU): 280V d.c.
 Battery-Box H 7.7, Battery-Box H 7.7(AU): 336V d.c.
 Battery-Box H 9.0, Battery-Box H 9.0(AU): 392V d.c.
 Battery-Box H 10.2, Battery-Box H 10.2(AU): 448V d.c.
 Battery-Box H 11.5, Battery-Box H 11.5(AU): 500V d.c.

Recommended Charging

Current By Manufacturer:	5A
Maximum Charging Current:	25A
Maximum Discharging Current:	25A
Rated Capacity:	25Ah

Tested according to:

EN 61000-6-3:2007/A1:2011
 EN 61000-6-1:2007